



HG - 6

EXTRA POWERFUL ACID FOR LIMESTONE CRUSTS

APPLICATIONS:

H G - 6 is composed of a synergized mixture of acids to eliminate limestone crust and deposits of cement.

Eliminates all insoluble salts and oxides.

An aggressive product that needs to be handled by special workers.

Contains very effective anticorrosion and retardant action to allow the product to work and reduce fumes.

INSTRUCTIONS:

FLOORS: Use from 10 to 25 % in automatic machines.

Let it work 10 mins. and check if action is completed.

Do not leave product to dry. At the end of the work, rinse and neutralize the surface with an alkaline solution.

BOILER: CONSULT OUR TECNICIANS FOR A CORRECT USE.

Recycle solution from 30 to 50 % for 60 - 90 mins.

The quantity of crust determines time and concentration of use.

After treatment, rinse and neutralize treated surfaces with a solution of caustic soda at 1 %.

Can be used on heat exchange equipment, bottle washer, boilers etc ..

Do not use on soft metals, such as cooper, aluminium and light alloys.

Do not use on marbles on stone floors. Can be used on terracotta.

CHEMICAL - PHSYCAL DATA :

Status: Liquid
pH.: 2 to 1 %

Foam: low
Colour: Orange
Odour: Spicy

COMPONENTS :

Inorganic acids, anticorrosive agent
non-ionic surfactants

CAUTION :

Wear clothes and gloves, protect eyes and face

Corrosive. Causes severe burns. In case of contact with eyes or face rinse immediately with plenty of water and seek medical advice.

Keep away from alkaline or chlorine products.

R 35 - Causes severe burns. S 36 - Wear protective clothes.

S 23 - Do not inhale gas, fumes or vapours.

S 26 - In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

